

DL-0242-9

30/5/21/87 JEM

3 J. J. MURRAY

U-25

08.02

2-168

THE COMPLETED DESIGN OF THE SLC FINAL FOCUS SYSTEM*

J. J. MURRAY, K. L. BROWN AND T. FIEGUTH
Stanford Linear Accelerator Center
Stanford University, Stanford, California 94305

SLAC-PUB--4219
DE87 009452

1. Summary

The design of the SLC Final Focus System has evolved from its initial conceptual design^{1,2} into its final form. This final design is described including a review of the critical decisions influencing the adoption of particular features. The creation of a feasible design has required that these decisions be tempered by practical considerations such as site constraints, correction of optical errors caused by imperfections, and accommodations requested by engineers and particle detector physicists. As this is the first such system to be built, it is hoped that the experience gained will be useful for the design of future systems.

2. Introduction

The part of the SLC between the ends of the arcs and the Interaction Point (IP) are called the Final Focus Systems (FFS). Overall, the functions of the FFS are to transform the beams at the ends of the arcs so as to form dispersion-free, round beams at the IP. This 1st order beam size is optimized to yield the maximum possible luminosity when the effects of various perturbations and aberrations have been accounted for and when 1st and 2nd order optical corrections have been applied. Site limitations required that length conserving measures be taken.

The FFS for electrons and positrons are essentially the same, each consisting of four subsystems as indicated in Fig. 1.

The functions of these subsystems are as follows:

THE FINAL FOCUS BEND (FFB)

- Removes dispersion which at the ends of the Arcs is given by $\eta_x = 0.0474\text{m}$ and $\eta_y = \eta'_x = \eta'_y = 0$.
- Transfers the Arc beams (with $\beta_x = 8.70\text{m}$, $\beta_y = 1.14\text{m}$ and $\alpha_{x,y} = 0$) to the next subsystem with a transfer matrix equal to the negative identity matrix.
- Provides a large, achromatic bend needed to satisfy global geometry constraints.
- Provides quad/skew-quad pairs separated in phase by $\sim \pi/2$ to remove the accumulated anomalous dispersion at the IP due to perturbations in the Arcs and FFS.

THE INITIAL TRANSFORMER (IT)

- Initial demagnification, and provides a round beam, with $\beta_{x,y} = 0.12\text{m}$ and $\alpha_{x,y} = 0$, to the next subsystem.
- Provides trims on the two last quadrupoles to adjust $\beta_{x,y}$ at the IP.
- Provides a region where the e^+, e^- pathlength difference was adjusted.

THE CHROMATIC CORRECTION SYSTEM (CCS)

- Corrects the dominant 2nd order chromatic aberrations at the IP without significantly introducing others.
- Provides a bend geometry to reduce synchrotron radiation (SR) background in the particle detector.
- Provides space for a low field soft bend magnet to further reduce SR background.

THE FINAL TRANSFORMER (FT)

- Completes the demagnification process. The magnification in this transformer is the same in the x and y planes, so that at the IP the ideal beam is round, with an optimum $\beta_{x,y} = 0.0075\text{m}$ and $\alpha_{x,y} = 0$.
- Allows independent adjustment of the axial position of the beam waist to match the position of temporal coincidence at the IP. This is done by trimming QD2B and QF3 quadrupoles (see Fig. 1).
- Provides a skew quad for suppression of cross-plane coupling between x, y' and x', y at the IP.

Details of the FT Design

This is the most critical subsystem of the FFS in terms of sensitivity to chromatic aberrations, misalignments and other errors. Described below is the procedure that led to the adopted design. It is based on the attractive symmetries that occur when symmetric quadrupole triplets are used as building blocks. A basic optical model was adopted consisting of two quarterwave sections in series which form a halfwave transform with a diagonal transfer matrix given by the equation:

$$\begin{pmatrix} 0 & F_{2,y} \\ -1/F_{2,y} & 0 \end{pmatrix} \begin{pmatrix} 0 & F_{1,y} \\ -1/F_{1,y} & 0 \end{pmatrix} = \begin{pmatrix} -M_{x,y} & 0 \\ 0 & -i/M_{x,y} \end{pmatrix} \quad (1)$$




Fig. 1. Schematic of the SLC Final Focus System.

*Work supported by the Department of Energy, contract DE-AC03-76SF00515.

MASTER

where $M_x = F2_x/F1_x$ and $M_y = F2_y/F1_y$. For the SLC

$$M_x = M_y = M \quad (2)$$

Consider the quarterwave section nearest the IP [see Fig. 1]. It consists of a close-packed symmetric triplet with equal drifts, ℓ' , on both ends. This close-packed feature was adopted to conserve overall length which is of special significance in the final transformer where the 2nd order chromatic aberrations, T_{126} and T_{346} , are very large each with a magnitude approximately equal to the overall length of the *unreduced* configuration (defined below). The center quadrupole is split in half longitudinally to avoid impractical length/bore ratios. All four quadrupoles have the same bore and pole tip field, to utilize the maximum practical gradient and to permit powering them in series.

The minimum value for the drift ℓ' between the downstream face of QF1 and the IP depends on the particle detector requirements. For conventional quadrupoles and the MKII detector, ℓ' must be ≥ 2.8 m for QF1 to clear the stray field of the detector solenoid. For this value of ℓ' it is estimated that a quadrupole bore radius of about 2 cm is required to clear both the charged and neutral components of a fully disrupted beam. In turn, a maximum allowable pole tip field, conservatively chosen as 10 kg for conventional quadrupoles, determines the maximum common field gradient of the triplet magnets.

Leaving ℓ' and the common gradient fixed, and taking advantage of the chosen fore/aft symmetry, two free parameters (the equal lengths of QF1 and QF3 and the equal lengths of the QD2's) are sufficient to generate the desired quarterwave section with length L .

Now, consider the upstream quarterwave section. Scaling the quarterwave section just found (all lengths by $1/M$ and the common gradient by M^2) and combining the two sections satisfies Eq. (1). With $1/M \sim 4$ or 5, however, this leads to an excessive overall length and excessive lengths of individual quadrupoles. We will refer to this as the *unreduced* configuration with overall length L_o given by,

$$L_o = \left(1 + \frac{1}{M}\right)L \approx 50 \text{ m}. \quad (3)$$

Steps are now taken to reduce these lengths to practical values:

- The quadrupole lengths are decreased by scaling the common gradient by an arbitrary factor which results in quadrupole lengths comparable to those in the downstream section. A four-fold adjustment is made using the lengths of QF4, QF6 and QD5A,B and the drifts $D2_{u,d}$ and $D3$ to satisfy Eq. (1). This maneuver has *no effect on overall length*.
- With a diagonal overall transfer matrix as given in Eq. (1), the foci can be moved in a coordinated fashion as follows with *no effect on the overall 1st order transfer matrix*.

$$\Delta \ell' \text{ (downstream)} = -M^2 \Delta D2_u \text{ (upstream)}. \quad (4)$$

With $D2_u$ decreased in this way, the overall length is decreased by $(1/M^2 - 1) \Delta \ell'$, where $1/M \sim 4$ or 5. It is desirable, however, to leave ℓ' fixed and compensate $\Delta D2_u$ another way. An approximate procedure is to adjust the lengths of QF1,3 and QD2A,B and QF4,6 and QD5A,B with the same result except for the appearance of non-zero matrix elements R_{21} and R_{43} in the overall transfer matrix (this deviates from the telescopic condition which was initially chosen to minimize chromatic aberrations). These matrix elements are very small ($\sim 0.1 \text{ m}^{-1}$) with no significant effect on the FT performance. Similarly, simultaneous reductions of drifts $D2_u$, $D2_d$ and $D3$ can be approximately compensated in the same fashion.

The overall length of the FT is thus reduced to an acceptable value $L_{FT} \approx 38$ m which still leaves space for a "soft" bend magnet, corrector dipoles, instruments and other required hardware. The drift $D3$ is chosen so that QF4,6 and QD5A,B become identical.

The Need for Chromatic Correction

It has been found using computer simulations that the only significant aberrations in the FT are those represented by the 2nd order matrix elements T_{126} and T_{346} . In the FT these terms are both almost equal to L_o to within about 10%, or

$$T_{126} \approx T_{346} \approx L_o = \left(1 + \frac{1}{M}\right)L \quad (5)$$

where L , the length of the quarterwave section nearest to the IP, has been uniquely determined by practical constraints.

The significance of these aberrations may be evaluated in terms of an "ideal" luminosity given by

$$\mathcal{L} = \left(\frac{N^2 f}{4\pi}\right) \frac{1}{\sigma_x \sigma_y} \quad (6)$$

where N is the number of particles per pulse in each beam, f is the pulse repetition rate and $\sigma_x \sigma_y$ is a measure of the transverse beam size at the IP.

With an unaberrated ideal beam entering the FT ($\beta_x = \beta_y = \beta$, $\alpha_x = \alpha_y = 0$ and $\epsilon_x = \epsilon_y = \epsilon$) we include the effect of the aberrations in the expression $\sigma_x \sigma_y$ by writing

$$\sigma_x \sigma_y \approx \langle x^2 \rangle \approx \langle y^2 \rangle \approx \left[M^2 \beta + \left(1 + \frac{1}{M}\right)^2 L^2 \sigma_i^2 / \beta \right] \epsilon \quad (7)$$

where σ_i is the rms momentum spread of the beam. This equation as a function of M (with β constant) has a minimum when

$$\frac{\sqrt{1+M}}{M^2} = \frac{\beta}{L\sigma_i} \quad (8)$$

with a corresponding β^* at the IP given by

$$\beta^* = M^2 \beta = L\sigma_i \sqrt{1+M} \quad (9)$$

Then, for the following optimistic parameter values:

$$\beta = 0.12 \text{ m}, \quad L = 10.7 \text{ m},$$

$$N = 5 \times 10^{10}, \quad f = 180 \text{ Hz},$$

$$\sigma_i = 2 \times 10^{-3}, \quad \text{and} \quad \epsilon = 3 \times 10^{-3} \text{ rad-m},$$

the optimum value of M would be

$$M = 0.46 \quad \text{with} \quad \beta^* = 0.026 \text{ m}, \quad (10)$$

and the expected luminosity becomes,

$$\mathcal{L}_{\max} = 2.3 \times 10^{29} \text{ cm}^{-2} \text{ sec}^{-1} \quad (11)$$

A design value for \mathcal{L} that is this low is unacceptable and shows the need to correct these 2nd order chromatic aberrations.

DISCLAIMER

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

Design of the CCS

The need to correct the unavoidable 2nd order aberrations inherent in the FT led to the introduction of the CCS. This chromatic correction section, just upstream of the FT is designed to introduce regions of dispersion where sextupoles can be used to cancel the overall T_{126} and T_{346} matrix elements for the combined FT and CCS.

The optical model adopted for the CCS is that of a modified Second Order Achromat² (SOA) consisting of four cells with an overall unit magnification. These cells are identical to each other with respect to quadrupole and sextupole components. The quadrupoles are placed to form geometrically symmetric doublets with equal strengths of opposing sign.

The two sextupoles in each cell are also identical in strength and placement to those in the other cells. This ensures that the 2nd order geometric aberrations from the sextupoles will be cancelled overall. In principle, only those sextupoles separated by the negative of the identity matrix (i.e., 1st-3rd and 2nd-4th cells) need be identical. The sextupoles are placed as close to the quadrupoles as practically possible to maximize their respective coupling to the T_{126} and T_{346} matrix elements and are separated by only an intervening drift to reduce sensitivity to misalignment. The strengths of the two sextupole families are now increased from the values for an SOA thus introducing aberrations in the CCS which will cancel those in the FT. Thus for an FT magnification of M it can be shown that,

$$T_{126})_{\text{overall}} = T_{126})_{\text{FT}} - M T_{126})_{\text{CCS}} = 0 \quad (12)$$

$$T_{346})_{\text{overall}} = T_{346})_{\text{FT}} - M T_{346})_{\text{CCS}} = 0 \quad (13)$$

In addition to increasing the sextupole strengths, the CCS achromat is further modified by longitudinal displacement of the dipole components. For a true SOA, there are identical bends in each cell. However, this places some bends in regions where both β and dispersion are large. Such placement leads to severe emittance growth caused by quantum fluctuations in the synchrotron energy loss. To mitigate this effect, all bends are located near the foci of the CCS lattice as shown in Fig. 1.

A second reason for this placement stems from the 2nd order optics: because we have now deviated from a true SOA it becomes necessary to deal with the chromatic matrix elements T_{166} and T_{366} in the CCS. It can be shown that if the dispersion is made to be identical in the first and second halves of the CCS, i.e., sequentially symmetric, these matrix elements will vanish. In the CCS the effective bend centers must coincide with the foci. Deviations of only a few centimeters will result in significant values for T_{166} and T_{366} with resulting loss of luminosity.

Suppression of emittance growth due to quantum fluctuations requires that bend strengths should be minimized. However, the sextupole strengths vary inversely with bend strength and are limited by a maximum practical value or the onset of higher order geometric aberrations. At full SLC energy, the strongest sextupoles are near the maximum practical strength. For this case loss of luminosity due to quantum fluctuations in the CCS bands alone is ~ 15%.

Third Order Considerations

The adopted disposition of sextupoles in the SLC CCS is the best that could be found which satisfies all of the foregoing criteria, and at the same time minimizes the dominant residual

3rd order chromatic aberrations, T_{1266} and T_{3466} , which limit the ultimate luminosity that can be achieved. The loss of luminosity due to these aberrations is ~ 20% for a momentum spread of $\sigma_E = 0.5$ percent. The largest residual 3rd order geometric aberrations T_{1274} and T_{3474} cause a corresponding loss of ~ 10%.

The origin of the residual 3rd order chromatic aberrations is interesting and suggestive of a procedure to reduce them. One of us (KLB) has shown that the overall 2nd and 3rd order chromatic aberrations are related to the intrinsic aberrations of the FT and CCS as follows.

$$T_{1266})_{\text{overall}} = T_{1266})_{\text{FT}} + T_{126})_{\text{FT}} T_{226})_{\text{CCS}} + T_{116})_{\text{FT}} T_{126})_{\text{CCS}} - M T_{1266})_{\text{CCS}} \quad (14)$$

$$T_{3466})_{\text{overall}} = T_{3466})_{\text{FT}} + T_{346})_{\text{FT}} T_{346})_{\text{CCS}} + T_{236})_{\text{FT}} T_{346})_{\text{CCS}} - M T_{3466})_{\text{CCS}} \quad (15)$$

When the sextupoles are powered in a two-family configuration and adjusted so that $T_{1266})_{\text{overall}}$ and $T_{3466})_{\text{overall}}$ vanish, the 3rd order residuals, $T_{1266})_{\text{overall}}$ and $T_{3466})_{\text{overall}}$, do not vanish. In fact, they are significant and limit the momentum acceptance of the system. The dominant contributions come from the 2nd order products, $T_{126})_{\text{FT}} T_{226})_{\text{CCS}}$ and $T_{346})_{\text{FT}} T_{346})_{\text{CCS}}$, and not from the intrinsic 3rd order terms. This suggests that with the sextupoles powered in a four-family configuration and adjusted so that $T_{226})_{\text{CCS}}$ and $T_{346})_{\text{CCS}}$ as well as $T_{126})_{\text{overall}}$ and $T_{346})_{\text{overall}}$ vanish, the 3rd order residuals might be suppressed. Suppression factors as large as 5 have been observed in computer simulations but at the expense of excessive sextupole strengths and a significant increase of 3rd order geometric aberrations. So—this procedure has been of no practical value to our present design.

Conclusions

The final design of the FFS is both practical and shown to be effective in eliminating 2nd order aberrations. Other luminosity degrading effects still remain, namely, 3rd order chromatic and geometric aberrations, emittance growth due to quantum fluctuations, and the effects of component misalignment and fabrication errors.

We believe that within the framework of our optical model a compromise has been achieved which minimizes sensitivity to these effects. For a perfect beam entering the FFS with the following parameters: $E = 50$ GeV, $\sigma_E = 5 \times 10^{-3}$, $\epsilon = 3 \times 10^{-10}$ rad-m, $f = 180$ Hz and $N = 5 \times 10^{10}$ particles/pulse in each beam (with perfect register and no pinch) residual aberrations and quantum fluctuations contribute more or less equally and limit the luminosity to $\sim 1 \times 10^{30}$ cm⁻² sec⁻¹. If reasonable construction tolerances are met and 1st order optical corrections are successfully applied the effect of errors could be negligible.

References

1. SLC Design Handbook, December 1984.
2. Proceedings of the SLC Workshop SLAC-Report-247, March 1982.
3. K. L. Brown, SLAC-PUB-2257, February 1979.