

CONF-870610--23

PHOTON ENERGY TUNABILITY OF ADVANCED PHOTON SOURCE UNDULATORS\*

P. J. Viccaro and G. K. Shenoy  
Argonne National Laboratory  
Argonne, IL 60439

CONF-870610--23

August 1987

DE88 010045

The submitted manuscript has been authored by a contractor of the U. S. Government under contract No. W-31-109-ENG-38. Accordingly, the U. S. Government retains a nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or allow others to do so, for U. S. Government purposes.

This manuscript submitted to the 5th National Conference on Synchrotron Radiation Instrumentation, Univ. of Wisconsin-Madison, WI., June 22-25, 1987; and to be published as part of the Conference proceedings in Nucl. Inst. and Methods.

**DISCLAIMER**

This report was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed, or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.

\*This work supported by the U.S. Department of Energy, BES-Materials Sciences, under Contract W-31-109-ENG-38.

**MASTER**

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

P. J. Viccaro and G. K. Shenoy  
Argonne National Laboratory  
Argonne, IL 60439

ABSTRACT

At a fixed storage ring energy, the energy of the harmonics of an undulator can be shifted or "tuned" by changing the magnet gap of the device. The possible photon energy interval spanned in this way depends on the undulator period, minimum closed gap, minimum acceptable photon intensity and storage ring energy. The minimum magnet gap depends directly on the stay clear particle beam aperture required for storage ring operation. The tunability of undulators planned for the Advanced Photon Source with first harmonic photon energies in the range of 5 to 20 keV are discussed. The results of an analysis used to optimize the APS ring energy is presented and tunability contours and intensity parameters are presented for two typical classes of devices.

---

\*This work supported by the U.S. Department of Energy, BES-Materials Sciences, under Contract W-31-109-ENG-38.

## I. INTRODUCTION

The relationship between the energy tunability of an undulator and the storage ring energy,  $E_R$  has been investigated previously [1,2,3] for the specific case of the Advanced Photon Source (APS) to be built at Argonne. As was shown, both the tunability as well as the fundamental undulator photon energy are determined by the period,  $\lambda$ , of the device, the magnetic gap,  $G$ , and  $E_R$ . The minimum ring energy necessary to provide a given tunability interval around a particular photon energy of the undulator can be uniquely specified given the minimum acceptable photon flux and minimum achievable magnet gap. The latter parameter in turn, depends on the particle beam aperture required for operation of the storage ring.

For a majority of the undulators on the APS, the photon energies will span the energy range of approximately 5 to 20 keV. The obvious requirement is to achieve this energy span on a given beam line with as few undulators possible. As has been discussed, the tunability of a single device increases with increasing ring energy. Obviously, there exists a minimum  $E_R$  below which the tunability criteria are not satisfied. An unambiguous determination of this minimum  $E_R$  is essential if a realistic choice of the storage ring energy is to be made.

For the case of the APS, the ring energy will be (7+10%) GeV [4]. This value is based on an analysis similar to the one described above. The undulator tunability characteristics used were (1) the availability of first harmonic photon energies in the interval of approximately 4.7 to 14 keV from a single device, and (2) the availability of 20 keV first harmonic radiation from a second device with limited tunability [3]. Both criteria are satisfied at the proposed APS ring energy and expected storage ring aperture.

In the following, we present a brief summary of the optimization procedure used in the analysis and discuss the photon energies and intensity characteristics of two types of undulators planned for the APS.

## II. ANALYSIS

The energy in keV of the  $i^{\text{th}}$  harmonic of an undulator for an observation point along the midplane axis of the device is given by: [5,6]

$$E_{Pi} = \frac{0.949 E_R^2 i}{\lambda(1 + K^2/2)} \quad (1)$$

Where  $E_{Pi}$  is photon energy in keV,  $E_R$  is the ring energy in GeV,  $\lambda$  is the undulator period in cm and  $i$  is the harmonic number. We will consider only the first harmonic  $i = 1$  and  $E_{P1} = E_p$ . The deflection parameter  $K$  is given in terms of the undulator period (in cm) and the peak magnetic field  $B_0$  (in Tesla) by

$$K = 0.934 \lambda B_0 \quad (2)$$

$K$  is related to the maximum deflection angles (slope) of the particles trajectory through the undulator and is closely seated to the photon intensity the device delivers at the harmonics. For hybrid magnets based on permanent magnet blocks and permendur pole tips,  $B_0$  is given by [7]

$$B_0 = 0.95 a \exp(-G/\lambda(b-cG/\lambda)) \quad (3)$$

where  $G$  is the magnet gap of the undulator in cm.

In Eq. 4, the factor 0.95 represents the "filling factor" which approximates the packing factor of high-permeability blocks in the undulator assembly. The constants a, b and c depend on the magnetic material and are given in Table 1 for two permanent magnet candidate materials, SmCo<sub>5</sub>/permendur and Nd-Fe-B permendur.

---

TABLE 1

Constants used in Eq. 3 for Hybrid Magnetic based on REC or Nd-Fe-B

---

	REC/Hybrid	Nd-Fe-B
a (T)	3.33	3.44
b	5.47	5.08
c	1.8	1.54

---

Equation 3 for the peak field is valid in the interval  $0.07 < G/\lambda < 0.7$ . Although the upper limit for  $G/\lambda$  does not define the maximum operational gap of the device, for small period devices ( $\lambda < 3$ ), the K-values and, hence, photon intensities are small. Therefore, the operational limits of a given device are usually near the upper gap to period ratio.

Equations 1, 2, and 3 form a set of coupled equation which determine the photon energy of a given harmonic as a function of gap, device period and ring energy. At a given ring energy  $E_R$ , the undulator period and gap, determine the on-axis 1st harmonic energy,  $E_p$ . Decreasing the gap increases  $B_0$  and hence the value of K resulting in a lower photon energy.

In summary, the largest photon energy occurs at the largest gap for a given undulator period and has both the smallest K and intensity. The energy may be shifted down from this maximum by decreasing the gap. The K-value and

therefore photon intensity increase with decreasing gap. The tunability from the maximum to minimum photon energy is limited by the maximum gap determined by the minimum acceptable intensity from the fundamental of the undulator and the minimum gap determined by the ring aperture. In addition, the tunability interval depends on the storage ring energy.

At any given  $E_R$ , the maximum desired photon energy,  $E_U$  and minimum deflection parameter,  $K_U$ , at the open gap ( $G_U$ ) position determine the required device period,  $\lambda(E_R)$  at each ring energy. This value of  $\lambda$  is the maximum one at  $E_R$  capable of producing  $E_U$  and is also the one with the largest tunability range consistent with  $E_U$  and  $K_U$  because it has the smallest closed-gap to  $\lambda$ -ratio. Once this period is determined for  $E_U$ , then the gap at each  $E_R$  required to produce any  $E_P$  smaller than  $E_U$  can be determined. In particular, the minimum gap,  $G_L$ , then determines the minimum possible first harmonic photon energy,  $E_L$ . The interval  $E_U-E_L$  is the tunability interval at a given  $E_R$ . The maximum interval possible within the constraints on  $K_U$  is that provided by the period determined above.

Once a particular photon energy interval is chosen, e.g., 4.7 to 14 keV first harmonic tunability, then it is clear that within the constraints on  $K_U$  and the closed gap  $G_L$ , there is a minimum ring energy at which this tunability can be achieved. As mentioned, this minimum  $E_R$  is important in deciding the optimum ring energy.

Within this analysis, there is an equivalent way of analyzing the tunability vs. ring energy questions which involves solutions to Eq. 1 with the constraints imposed by the tunability criteria. For example,  $E_L$  be the minimum photon energy at the closed gap position  $G_L$  of the undulator. Let  $E_L = fE_U$  where  $f < 1$ ; then the expressions for the fundamental on-axis energies of the undulator result in the equation

$$f\left(1 + \frac{K_L^2}{2}\right) = \left(1 + \frac{K_U^2}{2}\right). \quad (4)$$

The value of  $K_U$  is either a minimum acceptable K-value or that determined by a maximum gap/ $\lambda$  value. In either case, if the minimum gap value is specified, then Eq. 4 determines a unique undulator period which is independent of the photon energy and the ring energy. This is the smallest period for which  $E_L$  will be achieved at  $G_L$ . It also yields the largest K-value at  $E_L$ . This minimum undulator period also corresponds to the minimum ring-energy at which the tunability range  $E_U - E_L$  will be achieved. At higher ring-energies, the same photon energy interval can be spanned with devices with periods larger than the minimum  $\lambda$  given by Eq. 4.

For example, consider the case of a SmCo<sub>5</sub>-Hybrid undulator maximum  $G_U/\lambda = 0.7$ . Then we have  $K_U = 0.1551\lambda$ . Suppose the minimum gap is  $G_L = 1.5$  cm, and the desired  $E_L/E_U$  corresponds to  $f = 0.5$ . Then the solution of Eq. 4 is  $\lambda = 3.73$  cm. If a 14 to 7 keV tunability is required from this device, then a minimum ring energy of  $E_R = 8.01$  GeV is required. Following this procedure, in Table 2 has been constructed for several tunability ranges from the value maximum of  $G_U/\lambda = 0.7$  to the minimum gap  $G_L$ .

TABLE 2

Values of minimum ring-energies  $E_R$  period  $\lambda$  and K-values for the various tunability intervals and minimum gap values,  $G_L$  for undulators. The largest gap considered,  $G_U$ , was determined by the maximum gap to period ratio of 0.7. The values for Nd-Fe-B devices are given in parenthesis below those for a SmCo<sub>5</sub>-Hybrid one.

$E_p$ (keV)	$E_L$ (keV)	$G_L$ (cm)	$G_U$ (cm)	$\lambda$ (cm)	$K_U$	$K_L$	$E_R$ (GeV)
14	14	1.5	-	2.143	0.33 (2.143)	- (0.40)	5.78 (5.84)
14	7	1.5	2.61 (2.50)	3.730 (3.574)	0.57 (0.66)	1.63 (1.70)	8.01 (8.01)
14	7	1.4	2.49 (2.38)	3.559 (3.407)	0.55 (0.63)	1.62 (1.67)	7.78 (7.76)
14	7	1.3	2.37 (2.27)	3.386 (3.239)	0.53 (0.60)	1.60 (1.65)	7.54 (7.51)
14	8	1.5	2.48 (2.38)	3.541 (3.393)	0.55 (0.63)	1.42 (1.48)	7.75 (7.74)
14	9	1.5	2.35 (2.26)	3.363 (3.223)	0.52 (0.60)	1.24 (1.29)	7.51 (7.49)
14	4.7	1.0	2.31 (2.21)	3.297 (3.152)	0.51 (0.58)	2.19 (2.24)	7.42 7.38
20	20	1.5	- -	2.143 (2.143)	0.33 (0.40)	- -	6.90 (6.98)
20	14	1.0	1.70 (1.63)	2.434 (2.323)	0.38 (0.43)	1.03 (1.06)	7.41 (7.31)

As is evident from Table 2, the Nd-Fe-B-Hybrid undulator results in a larger K-values compared to those for SmCo<sub>5</sub>-Hybrid, but does not significantly alter the minimum ring energy necessary to achieve the desired tunability range at the maximum gap condition if  $G_U/\lambda = 0.7$ . Hence, a Nd-Fe-B device will always have a higher photon flux than the equivalent SmCo<sub>5</sub> one, as expected from previous analyses.

However, if the gain in peak field achieved with Nd-Fe-B is offset by larger open gap ratio then for the same initial  $K_U$  and period for both devices, the Nd-Fe-B undulator will have a larger tunability interval than the corresponding SmCo<sub>5</sub> one. This reflects directly in the minimum ring energy necessary to achieve a given tunability interval. The maximum gap to period ratio for the case for equal peak field is  $G_U/\lambda = 0.76$  for Nd-Fe-B.

A final aspect of this analysis which is pertinent to the radiation characteristics of APS undulators is the total possible photon energy spans of devices with a certain fundamental photon energy. That is, a first harmonic of say 20 keV is achievable by any undulator whose period falls within certain limits for a given ring energy. However, each device will produce this radiation at this energy at a value of the magnet gap which depends on the period of the device. Each device has, therefore, a unique tunability interval which includes 20 keV. The actual tunable range depends, as usual, on the open and closed gap constraints. For a given ring energy, the contours of a first harmonic photon energy versus undulator period have maximum and minimum values determined by the open magnet gap K-values and minimum closed gap. All possible photon energies which include 20 keV are determined in this way.

The result for 20 keV are shown in Fig. 1 for specific ring energies ranging from 8 to 6 GeV and Nd-Fe-B-Hybrid undulators. The area bounded by each contour is a measure of the tunability at that ring energy. The

radiation of the devices represented in the figure include 20 keV photons from the first harmonic in this example. As is evident, tunability at this photon energy range is severely restricted at 6 GeV.

The K-value and hence photon intensity is not the same for each device at 20 keV. As shown in Fig. 2, the K-value is largest at the largest period devices capable of delivering 20 keV.

The contours are shown in Fig. 3 for Nd-Fe-B Hybrid undulators with first harmonic radiation which includes 14 keV. The tunability of the devices becomes significant at 7 GeV and above. In addition, the K-value at 14 keV shown in Fig. 4 for the ring energies indicated imply significant intensity in the second and third harmonics of these undulator. This means that the effective tunability interval is two to three times larger than that implied by considering the fundamental only.

### 3. CONCLUSIONS

These preceding results indicate that for the APS at a ring energy of (7 + 10%) GeV large tunability intervals in the range of approximately 5 to 14 keV can be expected for devices with periods above 3 cm. In addition, the K-values larger than 1 can be expected at the lower photon energies. This implies that significant third (and second) harmonic radiation should be achievable which effective will extend the first harmonic tunability range to nearly three times the maximum first harmonic photon energy. We conclude from these results that the intensity contained in the second and third harmonic should be small and the total tunability of these undulators will be determined by the first harmonic radiation only.

## REFERENCES

1. P. J. Viccaro and G. K. Shenoy, "Undulator Tunability and Ring Energy", Argonne National Laboratory Report, Light Source Note LS-73 (1986).
2. P. J. Viccaro and G. K. Shenoy, "Undulator Tunability and Synchrotron Ring Energy", for press IEEE Trans. Nucl. Science.
3. G. Brown, Y. Cho, J. Hastings, S. Krinsky, D. Moncton, G. K. Shenoy and P. J. Viccaro, "Ring Energy Selection and Extra-Long Straight Sections for the Advanced Photon Source: A Report and Recommendations by the National Task Group", Argonne National Laboratory Report ANL-87-14 (April 1987)
4. "Conceptual Design Report: 7 GeV Advanced Photon Source", Argonne National Laboratory Report ANL 87-15 (April 1987).
5. For a recent review of undulator properties see S. Krinsky, M. L. Pearlman and R. E. Watson in Handbook on Synchrotron Radiation, Vol. 1a, ed. by E. E. Koch, North Holland, 1983.
6. G. K. Shenoy and P. J. Viccaro, "An Overview of the Characteristics of the 6 GeV Synchrotron Radiation: A Preliminary Guide to Users", Argonne National Laboratory Report ANL-85-69 (October 1985).
7. K. Halbach, "Application of Permanent Magnets in Accelerators and Electron Storage Ring" J. Appl. Phys. 57 (1985) 3605 and references therein.

## FIGURE CAPTIONS

- Fig. 1 A plot of achievable first harmonic photon energies which include 20 keV versus undulator period for the storage ring energies (a) 6 GeV, (b) 6.5 GeV, (c) 7 GeV, and (d) 8 GeV. The lower bound for a given contour is determined by the minimum gap of  $G_L = 1$  cm and the upper bound by the maximum ratio  $G_U/\lambda = 0.76$ .
- Fig. 2 A plot of K-values at 20 keV versus undulator period for the ring energies (a) 6 GeV, (b) 6.5 GeV, (c) 7 GeV, (d) 7.5 GeV, and (e) 8 GeV. The dashed line is determined by the minimum gap of  $G_L = 1$  cm.
- Fig. 3 A plot of achievable first harmonic photon energies which include 14 keV versus undulator period for the storage ring energies (a) 6 GeV, (b) 7 GeV, and (c) 7.5 GeV. The lower and upper bounds on each contour are the same as given in Fig. 1.
- Fig. 4 A plot of K-values at 14 keV versus undulator period for the ring energies (a) 6 GeV, (b) 6.5 GeV, (c) 7 GeV, and (d) 7.5 GeV. The dashed line as determined by the minimum gap of  $G_L = 1$  cm.







